

BELOW: COCO 600mm Ø PENDANT – STANDARD LED GLOBE SUPPLIED (non-dimmable)

## G95–12W

- Longer Life as 40,000 Hours
- Low Energy Consumption up to 90%
- Less Heat Output
- Good Light Distribution, Gentle and Even
- Environmental Friendly – No Harmful Mercury
- Shockproof
- UV and IR Free
- Low Maintenance Costs



**MODEL: LDG95E27–12W–DL, LDG95B22–12W–DL**

- Daylight 5000K
- Lumen: 1050 lm

**MODEL: LDG95E27–12W–WW, LDG95B22–12W–WW**

- Warm White 3000K
- Lumen: 1000 lm

### SPECIFICATION

- Angle: 270°
- Wattage: 12W
- Voltage/Frequency: 220V–240V 50/60Hz
- Electrical Current: 130mA
- Power Factor: >0.5
- CRI: >80
- Base: E27&B22

---

BELOW: COCO 400mm Ø PENDANT – STANDARD LED GLOBE SUPPLIED (non-dimmable)

## G70–8W

- Longer Life as 40,000 Hours
- Low Energy Consumption up to 90%
- Less Heat Output
- Good Light Distribution, Gentle and Even
- Environmental Friendly – No Harmful Mercury
- Shockproof
- UV and IR Free
- Low Maintenance Costs



**MODEL: LDG70E27–8W–DL, LDG70B22–8W–DL**

- Daylight 6500K
- Lumen: 650 lm

**MODEL: LDG70E27–8W–WW, LDG70B22–8W–WW**

- Warm White 3000K
- Lumen: 600 lm

### SPECIFICATION

- Angle: 270°
- Wattage: 8W
- Voltage/Frequency: 220V–240V 50/60Hz
- Electrical Current: 90mA
- Power Factor: >0.5
- CRI: >80
- Base: E27&B22