RETREAT 1.1

Technical Specifications

Designed for one person to work within, or two for a guick chat, RETREAT 1.1 is manufactured using sustainable timber frames and acoustic fabric panels in a range of colour combinations. Table top options are available as either a fixed or drop down version, and an inbuilt light with sensor controlled LED provides energy efficiency. Acoustic panels are used on both the interior and exterior to maximise acoustic performance. RETREAT comes without a floor base to allow for all users to enter the space without hinderance.



Low noise, sensor-controlled ventilation system with constant air exchange via top and base outlets with internal fan systems.



ENVIRONMENTAL DATA

60% recycled content to PET. Sustainably sourced timber FSC timber available on request.



SERVICES

Seamless mechanical services integration with allowances for a sprinkler and smoke detector.



RETREAT 1.1 requires 2 men for 2-3 hours.



PERFORMANCE

Acoustic materials used for internal and external surfaces provide ambient noise reduction and minimise noise reverberation from the surrounding office.



RETREAT sits flush on the floor with a rubber seal for acoustic protection, there is no step or floor base to incumber entry.



PLUG AND PLAY
Quick connect: Quick connection to mains power using standard sockets.





WARRANTY

7 year structural warranty.



PRODUCT DATA





Product dimensions

External dimensions 1136/1450W x 1120D x 2178mmH Internal dimensions 970/1286W x 990D x 2092mmH 1-2

People

Ventilation

QTY of fans 4 total; 2 draw in through

side, 2 draw out through

ceiling

Air flow rate 117.2CFM Power usage 5.76W Input 24V DC

User motion detected to 30sec / 3min / 10min

Power

Mains supply 10 amps Cord from booth 2 metres

2 gang; 1x Power, 1x USB A, 1x USB C Output

Socket options

AUS





Lighting

Power usage 9.6W 24V Input 85lm/W Lumen output LED options Warm or cool User motion detected to 30sec / 3min / 10min

Motion sensor

Passive infrared sensor

Running time options 30sec / 3min / 10min

PET

100% PET, 60-68% recycled Composition Sustainability Greentag certified. Greenrate level: A

VOC Emission $<0.004 \text{mg/m}^2/\text{hr}$

Structure

Faced plywood 60mm birch plywood Internal Acoustic wall covering External Acoustic wall covering

Door

Door dimensions 718/876W x 2068H x 8mm frameless toughened glass

Door weight 23kg

Disabled access No wheelchair access - disability accessible

Door latch Stainless steel magnet latch Drop seal Engaged when door is closed

Floor

Levelling Adjustable glides

Floor No floor - sealed perimeter

Install

Time 2-3 hours

2 People required

Fire safety

Fire alarm To be installed on request Smoke detection To be installed on request Sprinkler compatible To be installed on request

Cleaning

PET / Upholstery Timber

Refer to product care and maintainence guide Refer to product care and maintainence guide



OPTIONS & FINISHES

RETREAT 1.1 back options







PET back

RETREAT 1.1 table options



Fixed table Dimensions Height from floor

988x335x30mm 1005mmH



Fold down table Dimensions Height from floor

775x400x20mm 1045mmH

Timber finishes



Natural



Black Stain



Blazer Silcoates Blazer Surrey



Blazer St Andrews

Acoustic panel standard finishes







Sofa upholstery finishes

Silica Beige 454 Dune Beige 402 Boulder Grey 442 Granite Grey 452 Slate Blue 365



Acoustic panel seasonal finishes



Dulcie 908



Welford 101



Otway 458



Davenport 444



Cape Byron 577



Eyre 487



Ruby Gap 269



Wollumbin 550



Grampian 349



SQUARE BEAR

© Copyright 2021 All Rights Reserved

HEAD OFFICE

Unit 6/80 Jedda Road, Prestons New South Wales 2170, Australia P: +61 (0)2 9189 1444 sales@square-bear.com

SYDNEY SHOWROOM

120 Bourke Street, Woolloomooloo New South Wales 2011, Australia

www.square-bear.com

