## RETREAT 2.2

# Technical Specifications

For meetings of up to six people, RETREAT 2.2 accommodates various furniture styles, configurations, and integrated AV and IT options. RETREAT 2.2 is ideal for large meetings and collaborative tasks.



Low noise, sensor-controlled ventilation system with constant air exchange via top and base outlets with internal fan systems.



#### **ENVIRONMENTAL DATA**

60% recycled content to PET. Sustainably sourced timber FSC timber available on request.



#### SERVICES

Seamless mechanical services integration with allowances for sprinklers and smoke detector.



RETREAT 2.2 requires 2 men for 4-5 hours.



#### **PERFORMANCE**

Acoustic materials used for internal and external surfaces provide ambient noise reduction and minimise noise reverberation from the surrounding office.



#### **ACCESS**

RETREAT sits flush on the floor with a rubber seal for acoustic protection, there is no step or floor base to incumber entry.



#### **PLUG AND PLAY**

Quick connection to mains power using standard sockets.





#### WARRANTY

7 year structural warranty.



## PRODUCT DATA





#### **Product dimensions**

External dimensions 2135/2450W x 2180D x 2180mmH Internal dimensions 1970/2286W x 2050D x 2092mmH 4-6

People

Ventilation

QTY of fans 8 total; 4 draw in through

side. 4 draw out through

ceiling

Air flow rate 234.4 CFM Power usage 11.52W Input 24V DC

User motion detected to 30sec / 3min / 10min

#### Power

Mains supply 10 amps Cord from booth 2 metres

3 gang; 2x Power, 1x USB A, 1x USB C Output

#### **Socket options**

AUS





#### Lighting

Power usage 9.6W 24V Input 85lm/W Lumen output LED options Warm or cool User motion detected to 30sec / 3min / 10min

**Motion sensor** Passive infrared sensor

Running time options 30sec / 3min / 10min

#### **PET**

100% PET, 60-68% recycled Composition Sustainability Greentag certified. Greenrate level: A

**VOC** emission  $<0.004 \text{mg/m}^2/\text{hr}$ 

#### Structure

Faced plywood 60mm birch plywood Internal Acoustic wall covering External Acoustic wall covering

#### Door

Door dimensions 1009W x 2068H x 8mm frameless toughened glass

Door weight 40kg

Disabled access Wheelchair accessible Door latch Stainless steel magnet latch Drop seal Engaged when door is closed

#### Floor

Levelling Adjustable glides

Floor No floor - sealed perimeter

#### Install

Time 4-5 hours

People required 2

#### Fire safety

Fire alarm To be installed on request Smoke detection To be installed on request Sprinkler compatible To be installed on request

#### Cleaning

PET / Upholstery Refer to product care and maintainence guide Timber Refer to product care and maintainence guide



## OPTIONS & FINISHES

#### **RETREAT 2.2 back options**







PET back

#### **RETREAT 2.2 table options**



Meeting table low Dimensions Height from floor



Meeting table high Dimensions Height from floor

1500x700x25mm 1050mmH

#### **Timber finishes**



Natural



Black Stain





Blazer Silcoates Blazer Surrey



Blazer St Andrews

#### **Acoustic panel standard finishes**







Silica Beige 454 Dune Beige 402 Boulder Grey 442 Granite Grey 452 Slate Blue 365



#### **Acoustic panel seasonal finishes**



Dulcie 908



Welford 101



Otway 458



Davenport 444



Cape Byron 577



Eyre 487



Ruby Gap 269



Wollumbin 550



Grampian 349



1500x700x25mm

720mmH

### **SQUARE BEAR**

© Copyright 2021 All Rights Reserved

### **HEAD OFFICE**

Unit 6/80 Jedda Road, Prestons New South Wales 2170, Australia P: +61 (0)2 9189 1444 sales@square-bear.com

### **SYDNEY SHOWROOM**

120 Bourke Street, Woolloomooloo New South Wales 2011, Australia

www.square-bear.com

