

Model Sheet

	<div><div>Finish</div><div><div><div></div><div>23 Warm White</div><div>NCS S 0502-Y50R</div></div><div><div></div><div>24 Beige M1</div><div>NCS S 2005-Y50R</div></div><div><div></div><div>36 Soft Pink</div><div>NCS S 1010-Y50R</div></div></div></div>	<div><div>Lighting effect</div><div>Volumetric Diffuser</div><div>Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface</div><div>Photometric Data</div><div><div>Efficiency</div><div>44.11 lm/W</div></div><div><div>Coordinate System</div><div>CG</div></div><div><div>Total Flux</div><div>103.22 lm</div></div><div><div>Maximum Value</div><div>23.46 cd</div></div></div>
	<div><div>LED temperature color</div><div>2700 K</div></div> <div><div>Dimming</div><div>Push</div></div> <div><div>Installation type</div><div>Plug-in</div></div>	
	<div><div>Materials</div><div>Body: Aluminum</div><div>Diffuser: Blown-glass</div></div> <div><div>LED</div><div><div>G</div><div>CRI>90 156.94 lm 104</div><div>2700 K</div></div></div> <div><div>Driver</div><div>Constant Voltage 100~240 V V</div><div>50~60 Hz HZ</div></div> <div><div>Remarks</div><div>Dimmer switch on the base. 3 step dimming.</div><div>Battery life: from 6 to 18 hours (depending on intensity).</div><div><div><div></div><div>F</div><div>Dimmer</div><div>LED</div></div><div><div><div></div><div>Li-ion</div><div>IP20</div><div>Bi-volt</div><div>Dry Location</div></div><div><div>50-60Hz</div><div><div></div><div>PUSH</div></div></div></div></div></div>	<div><div>Other Applications</div><div><div></div><div></div></div></div>
	<div><div>Application</div><div>Floor and Table Lamps</div></div> <div><div>Packaging</div><div>1 Box</div><div>0.32 m x 0.29 m x 0.169 m</div><div>Gross weighth 1.4</div><div>Net weighth 0.95</div><div>Vol. 0.0156</div></div>	

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty