# Origami




## 4500

Design By Ramón Esteve

ORIGAMI blends light functionality with an opportunity for artistic creation. With just two pieces, designers can create infinite compositions. With a single connection point between the pieces and simple surface mounting installation, you can make as many configurations as you desire. ORIGAMI lighting is rated for both outdoor (IP65) and indoor settings which you can construct to climb a wall or façade like ivy. The light source is LED, guaranteeing high-efficiency energy consumption.

# Model Sheet









LED temperature color

2700 K / 3500 K

NCS S 6005-G80Y

TRIAC Dimming

Instalation type Surface Canopy

Materials Shade: ABS

> Arm: PC- Polycarbonate Wall plate: PC- Polycarbonate

1x LED STRIP 6,3W 350mA Light source

 $\square$ 

LED CRI>90 756 lm 120

2700 K / 3500 K

Constant Current 350 110~277 Driver

V V 50~60 Hz HZ

Remarks A maximum of 30 modules can be

connected to a single connection point. For bigger compositions, check connection system.

IP65 50-60Hz ✓ TRIAC

**Application** Wall Lamps

**Packaging** 1 Box

0.36 m x 0.355 m x 0.13 m


Gross weigth 1.5 Net weigth 1.35 Vol. 0.0166


#### Lighting effect

Direct Surface Grazer Directed grazing light.



### Photometric Data





## Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty