



Crisp Flush Mount

Ceiling Flush Mounts

YOUR PRODUCT CODE

CR-FM-S10-AA01-27-10_TRIAC_120V-IP20

DESCRIPTION

Crisp's simple, iconic design is suitable for both wall and ceiling installation, indoors and outdoors. The solid glass shade, offered in a range of finishes, is distinguished by its scored surface, adding a subtle textural detail to the environment.

MATERIALS

Cast solid glass, aluminum

COLLECTION NOTES

Luminaire lumens listed are for AC input TRIAC control. DC input performance please see photometry downloads. Each form of cast glass is unique. We review each to ensure they conform to ASTM standards, which includes the presence of small air bubbles within the glass.

PRODUCT DIMENSIONS

5 in dia x 3.3 in D

PRODUCT WEIGHT

3.5 lbs / 2 kg

PERFORMANCE

Delivered Lumens 550 lm (Frosted) | 445 lm (White) | 106 lm (Chrome) | 52 lm (Copper)
Power Consumption 7.5W
Luminous Efficacy 71.7 lm/W (Frosted) | 58.1 lm/W (White) | 13.9 lm/W (Chrome) | 6.9 lm/W (Copper)
90 CRI
Full detail in [photometry summary](#).

CERTIFICATION

UL Listed
• Suitable for Wet Locations
• Suitable for Damp Locations
IP20
IP65
Declare (LBC Red List Approved)



LED LIFESPAN
50k hours

SPECIFICATION LOGIC

GLASS FINISH

White Interior	S10
Chrome Exterior	S11
Frosted	S12
Copper Exterior	S13

BACKPLATE FINISH

Natural Anodized	AA01
Black Anodized	AA04

COLOR TEMPERATURE

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

DIMMING / CONTROL / INPUT

10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
Low Voltage (Driver required, driver not included)	LV

IP RATING

IP 20	IP20
IP 65	IP65

DRAWINGS

CR-WS Crisp Sconce Dimension (Rotate 90 degrees for flush mount version)

