



# Dimple Sconce

Sconces

## YOUR PRODUCT CODE

DP-WS-S1-AA01-27-10\_TRIAC\_120V-IP 20

## DESCRIPTION

Dimple is a compact and flush-mounted sconce that casts a diffuse and soft, atmospheric light. It is cheekily named for the thick, domed circular diffuser embedded into its front face.

## MATERIALS

Cast solid glass, aluminum

## COLLECTION NOTES

Luminaire lumens listed are for AC input TRIAC control. DC input performance please see photometry downloads. Each form of cast glass is unique. We review each to ensure they conform to ASTM standards, which includes the presence of small air bubbles within the glass.

## PRODUCT DIMENSIONS

5 in dia x 3.3 in D

## PRODUCT WEIGHT

3 lbs / 1.6 kg

## PERFORMANCE

Delivered Lumens 278 lm (Frosted) | 237 lm (White) | 122 lm (Smoked) | 217 lm (Amber)  
Power Consumption 8.5W  
Luminous Efficacy 38.3 lm/W (Frosted) | 32.7 lm/W (White) | 16.9 lm/W (Smoked) | 29.1 lm/W (Amber)  
95 CRI (Smoked) 90 CRI (Frosted/White) 80 CRI (Amber)

## CERTIFICATION

ADA Compliant  
UL Listed

- Suitable for Wet Locations
- Suitable for Damp Locations

IP20  
IP65  
Declare (LBC Red List Approved)



Declare.

## LED LIFESPAN

50k hours

## SPECIFICATION LOGIC

### GLASS FINISH

Amber	S3
Frosted	S4
Smoked	S2
White Interior	S1

### BACKPLATE FINISH

Natural Anodized	AA01
Black Anodized	AA04

### COLOR TEMPERATURE

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

### DIMMING / CONTROL / INPUT

1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
Low Voltage (Driver required, driver not included)	LV
10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV

### IP RATING

IP 20	IP20
IP 65	IP65

## DRAWINGS

DP-WS Dimple Sconce Dimension

