

Queue Sconce

Sconces

YOUR PRODUCT CODE

QS-24-AA04-27-1_TRIAC_120V

DESCRIPTION

Queue is a linear LED pendant and sconce system with limitless potential, designed for flexible installation and an inviting presence. Originally conceived as an answer to the monotony of workplace systems, Queue exudes a welcoming light and rich beauty in the subtle, rounded facets of its surface.

MATERIALS

Textured PMMA lens, anodized aluminum body.

COLLECTION NOTES

This product is designed to be installed with a 2" x 4" single gang junction box. For 4" octagonal or round boxes, a Junction Box Cover Plate will be required and is sold separately. White Gold AA-02 requires minimum 20 business day lead time.

PRODUCT DIMENSIONS

24": 24 L x 3 W x 4 in D | 44": 44.5 L x 3 W x 4 in D

PRODUCT WEIGHT

8 lbs / 3.6 kg

PERFORMANCE

Delivered Lumens 24": 1940 Im | 44": 3936 Im Power Consumption 24": 24W | 44": 45W Luminous Efficacy 24": 81 Im/W | 44": 87 Im/W 90 CRI

CERTIFICATION

ADA Compliant

UL Listed

· Suitable for Damp Locations



LED LIFESPAN


50k hours

SPECIFICATION LOGIC

LENGTH	
24"	24
44"	44
PRIMARY FINISH	
Natural Anodized	AA01
Black Anodized	AA04
Custom Anodized	AAXX
Custom Powder Coated	PCXX
White Gold Anodized	AA02
COLOR TEMPERATURE	
2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35
4000K (cool white)	40
DIMMING / CONTROL / INPUT	
1% Dimming, 0-10V Control, 120V or 277V "Universal Input"	1_10V_UNV
1% Dimming, TRIAC / Forward Phase Control, 120V Input	1_TRIAC_120V
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input"	0.1_10V_UNV

QS-44 Queue 44" Sconce Dimension

DRAWINGS



QS-24 Queue 24" Sconce Dimension

