Topo Sconce

Sconces



50 Greene St New York NY 10013 T +1 212 388 1621 sales@rbw.com



For 2D & 3D drawings of all products, including CAD, Revit and IES files, please visit rbw.com

Generate Date: Fri Oct 20 2023

DESCRIPTION

Topo's elegant construction is both minimal and inviting, seamlessly joining an elliptical glass bulb to the unique visual textures of our circular backplate. Offered in a selection of rich earth tones ranging from Clay to Basalt, the backplate radiates with warmth as the light illuminates the organic patterns on its surface.

MATERIALS

Opal glass, wood and cement composite

COLLECTION NOTES

Each Topo plate is unique in pattern due to the nature of the material.

PERFORMANCE

468.1 lm
Power Consumption 7.1W
Luminaire Watts 7.1W
66 lm/W
90 CRI

LED LIFESPAN

50k hours

CERTIFICATION

ADA Compliant
UL Listed
Suitable for Wet Locations
IP65



Generate Date: Fri Oct 20 2023

NOTE ON IMAGERY

All product photos are made using the correlated color temperature (CCT) of 2700k. The actual color temperature experienced within your environment may vary based on other light sources and materials present.

PRODUCT DIMENSIONS

Medium: 12 x 12 x 3.2 in | Small: 8.5 x 8.5 x 3.2 in

PRODUCT WEIGHT

Small: 1.6 lbs | Medium: 2.6 lbs

DIMENSIONAL WEIGHT

Small: 2 lbs Medium: 3 lbs


Ellipse


Е

BACKPLATE FINISH


Oat	V1
Straw	V2
	V2 V3
Clay	
Basalt	V4
Rust	V5
сст	
2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35
DIMMING / CONTROL / INPUT	
Low Voltage (Driver required, driver not included)	LV
10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, TRIAC / Forward Phase Control, 120V Input	1_TRIAC_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input"	1_10V_UNV
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input"	0.1_10V_UNV
IP RATING	
IP 65	IP65


Drawings





TP Topo Sconce Medium





TP Topo Sconce Small