


Model Sheet



Optional : Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

Finish	18 Graphite ADAPTA RF 9913 WX
LED temperature color	3000 K
Dimming	Optical sensor / Casambi / DALI-2
Installation type	Surface Canopy
Materials	Profile: Aluminum Diffuser: Borosilicate
Light source	1 x LED STRIP 24V 20W G
LED	CRI>90 1742.4 lm 87.12 3000 K
Driver	Constant Voltage 110~240 V V 50~60 Hz HZ
Remarks	The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass. <div> <div> <div></div> <div>F</div> </div> <div>Dimmer</div> <div>LED</div> </div> <div> <div>IP20</div> <div>Bi-volt</div> <div>Dry Location</div> <div>50-60Hz</div> </div>
Application	Hanging lamps
Packaging	1 Box 0.87 m x 0.35 m x 0.37 m Gross weight 7,5 Net weight 5 Vol. 0.1126

Lighting effect

Volumetric Diffuser

Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface



Photometric Data