Puck wall art



5481

Design By Jordi Vilardell


Wall sconce formed by two circular bodies with a single electrical connection. Available in different lacquered aluminium and felt finishes.

LED temperature

Model Sheet







15 Grey L2 NCS S 2500-N 71 Grey Felt L1 & Grey Felt D1

NCS S 4020-Y60R

Dimming 1-10V / DALI-2 / Push / Casambi

2700 K / 3500 K

Instalation type Surface Canopy

Materials Shade: ABS Wall support: Aluminum

Light source 2 x LED STRIP 12,6W 700mA

E

LED CRI>90 2871.9 lm 94.22 2700 K / 3500 K

Driver Constant Current 700 110~240

V V 50~60 Hz HZ

Diffuser: PC- Polycarbonate

Remarks

A maximum of 8 modules can be connected to a single connection point. For bigger compositions,

point. For bigger compositions, check connection system.

Application Wall Lamps


Packaging 1 Box 0.68 m x 0.68 m x 0.2 m


Gross weigth 5.2 Net weigth 4.15 Vol. 0.0924 Lighting effect

360° Surface Grazer Full-circle grazing light.



Photometric Data





Efficiency Coordinate System Total Flux Maximum Value 56.12 lm/W CG 1664.84 lm 365.39 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty