


Model Sheet



Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

- Finish
- 42 Blue M1
NCS S 5010-B10G
 - 10 White
NCS S 0300-N
 - 47 Green L1
NCS S 4005-G80Y
 - 37 Terra Red
NCS S 4040-Y70R
 - 24 Beige M1
NCS S 2005-Y50R
 - 11 Black
NCS S 8500-N

LED temperature color 2700 K / 3000 K / 3500 K / 4000 K

Dimming 0-10V / Push; 1-10V / Casambi / DALI-2

Installation type Remote XXS / Surface Canopy / Built-in XS / Surface Free Wire

Materials Ceiling rose: Steel

Light source 1 x LED 9,3W 350mA



LED CRI>90 1041 lm 116
2700 K / 3000 K / 3500 K / 4000 K

Driver Constant Current 350 110~277
V V 50~60 Hz HZ

Remarks Surface

-   Dimmable  LED
 IP20  Multi-volt  50-60Hz  0-10V

Application Hanging lamps

Packaging 1 Box
0.35 m x 0.35 m x 0.26 m
Gross weighth 2.6
Net weighth 1.4
Vol. 0.0318

Lighting effect



Close Proximity - Flat Diffuser

Lighting applications for illumination in close proximity to the user



Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.



Other Applications

