





Design By Ramos & Bassols

The Spa wall or ceiling lamp projects a bright glare-free light thanks to the subtle fluted effect of its shade. The aluminium frame has a wide range of finishes to adapt to different interior designs.

## Model Sheet



Finish

25 Beige D1 NCS S 4005-Y50R



11 Black NCS S 8500-N



23 Warm White NCS S 0502-Y50R

LED temperature

2700 K / 3500 K

Dimming

DALI / 1-10V / CASAMBI

Instalation type

Remote basic

Materials

Diffuser: PMMA Body: Aluminum Ceiling rose: Aluminum

Light source

1 x LED STRIP 21,6W 600mA



LED

CRI>90 4818 lm 57,6 2700 K / 3500 K


Driver

600 220~240 V V 50~60 Hz











Ceiling Lamps

Packaging

1 Box 3.3 m x 0.1 m x 0.1 m Gross weigth 5.8 Net weigth 3.6

Vol. 0.033

## Lighting effect

## **General Lighting**

Lamp for general lighting that equally distributes the light in all directions.



## Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency Coordinate System Total Flux Maximum Value

60.77 lm/W CG 1607.97 lm

686.66 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

6,5 cm

301 cm