





Design By Ramos & Bassols

The Spa wall or ceiling lamp projects a bright glare-free light thanks to the subtle fluted effect of its shade. The aluminium frame has a wide range of finishes to adapt to different interior designs.

Model Sheet



Finish

23 Warm White NCS S 0502-Y50R



25 Beige D1 NCS S 4005-Y50R



11 Black NCS S 8500-N

LED temperature

2700 K / 3500 K

Dimming

1-10V / CASAMBI / DALI

Instalation type

Remote basic

Materials

Diffuser: PMMA Body: Aluminum Ceiling rose: Aluminum

Light source

1 x LED STRIP 21,6W 600mA



LED

CRI>90 3212 lm 57,61 2700 K / 3500 K


Driver

600 220~240 V V 50~60 Hz











Ceiling Lamps

Packaging

1 Box 2.3 m x 0.1 m x 0.1 m Gross weigth 4.2 Net weigth 2.6 Vol. 0.023

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency Coordinate System 60.77 lm/W CG 1071.98 lm

457.78 cd

Total Flux Maximum Value

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

6,5 cm

201 cm