


2642

Design By Arik Levy

Ceiling light where different cubic volumes meet or expand to provide flexible solutions, maintaining spatial order.

Model Sheet



Finish	21 Black Grey NCS S 7000-N
	15 Grey L2 NCS S 2500-N
LED temperature color	2700 K / 3000 K / 3500 K
Dimming	DALI-2 / Casambi / 1-10V

Installation type	Surface Canopy
-------------------	----------------

Materials	Body: Aluminum
	Diffuser: PC- Polycarbonate
	Profile: Aluminum

LED	D
	CRI>90 2700 K / 3000 K / 3500 K

Driver	Constant Voltage 110~240 V V 50~60 Hz HZ
--------	---

Remarks	Main input by the biggest box
---------	-------------------------------

  Dimmable LED


Application	Ceiling Lamps
-------------	---------------

Packaging	3 Box
	0.38 m x 0.61 m x 0.22 m
	Gross weight 9.8
	Net weight 7.95 Vol. 0.0947



Lighting effect

Hidden Diffuser

Subtly directed diffused light that generates a soft hierarchy of light on to the illuminated surface




Photometric Data



Efficiency	72.42 lm/W
Coordinate System	CG
Total Flux	4634.73 lm
Maximum Value	427.37 cd/klm

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com