

Model Sheet

Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish

-  16 Grey M1
NCS S 4500-N
-  37 Terra Red
NCS S 4040-Y70R
-  10 White
NCS S 0300-N
-  24 Beige M1
NCS S 2005-Y50R
-  21 Black Grey
NCS S 7000-N
-  15 Grey L2
NCS S 2500-N

LED temperature color 2700 K / 3000 K / 3500 K

Dimming NO DRIVER / Push; 1-10V; DALI / Casambi / DALI

Installation type Built-in XS / Remote XXS / Surface Free Wire / Surface Canopy

Materials LED support: Aluminum
Tube: Steel
Ceiling rose: Steel

Light source 1 x LED PLATE 10,5W 700mA


LED CRI>90 2900 lm 145
2700 K / 3000 K / 3500 K

Driver Constant Current 700 110~240
V V 50~60 Hz HZ



Application Hanging lamps

Packaging 1 Box
0.94 m x 0.31 m x 0.205 m
Gross weight 4.2
Net weight 1.55
Vol. 0.0597

Lighting effect

Reflected

Creation of visual hierarchies within the luminaire itself, emphasising the materiality and texture of the product

Photometric Data

Efficiency	48.13 lm/W
Coordinate System	CG
Total Flux	1169.89 lm
Maximum Value	433.69 cd