


Tube

6165

Design By Ichiro Iwasaki

VIBIA

Model Sheet



Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish

- 15 Grey L2
NCS S 2500-N
- 21 Black Grey
NCS S 7000-N
- 37 Terra Red
NCS S 4040-Y70R
- 24 Beige M1
NCS S 2005-Y50R
- 10 White
NCS S 0300-N
- 16 Grey M1
NCS S 4500-N

LED temperature color 2700 K / 3000 K / 3500 K

Dimming NO DRIVER / DALI / Push;
1-10V; DALI / Casambi

Installation type Built-in XS / Remote Micro / Surface
Canopy / Surface Free Wire

Materials LED support: Aluminum
Tube: Steel
Ceiling rose: Steel

Light source 1 x LED PLATE 13,5W 700mA



LED CRI>90 3480 lm 139,2
2700 K / 3000 K / 3500 K

Driver Constant Current 700 110~240
V V 50~60 Hz HZ



Application Hanging lamps

Packaging 2 Box
0.248 m x 0.403 m x 0.403 m
Gross weight 4,3
Net weight 1.65
Vol. 0.0447

Lighting effect

Reflected

Creation of visual hierarchies within the luminaire itself, emphasising the materiality and texture of the product

Photometric Data

Efficiency	51.14 lm/W
Coordinate System	CG
Total Flux	1447.46 lm
Maximum Value	576.19 cd

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com