Wireflow chandelier




0315


Design By Arik Levy

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with twenty LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



O4 Black RAL 9005

LED temperature color

2700 K / 3000 K /

3500 K

Dimming

Casambi / Push; 1-10V; DALI-2

Instalation type Surface Canopy

Materials Ceiling rose: Steel

Body: Aluminum Horizontal rods: Steel

Light source 20 x LED 4,48W 350mA

D

LED CRI>90 9805 lm 109

2700 K / 3000 K / 3500 K

Driver Constant Current 350 100~240

V V 50~60 Hz HZ

Remarks Driver: 350mA / TCI / MAXI JOLLY

US DALI 50 / 100/127V / 50/60Hz

IP20 Bi-volt 50-60Hz

Application Hanging lamps

Packaging 2 Box 1.633 m x 1.619 m x 0.086 m

Gross weigth 27.2 Net weigth 24.23 Vol. 0.3859


Lighting effect


Volumetric Diffuser

Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface




Photometric Data





Efficiency 40.11%
Coordinate System CG
Total Flux 9805
Maximum Value 53.87

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty