Wireflow free-form



0345

Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product.

Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. The electrical connection point can be positioned on the ceiling or wall

Model Sheet







Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

04 Black Finish RAL 9005

LED temperature color

2700 K / 3000 K / 3500 K

Dimming

Push; 1-10V / Casambi / DALI-2

Instalation type

Built-in XS / Surface Free Wire / Surface Canopy / Remote XXS

Materials

Rods: Steel Body: Aluminum Ceiling rose: Steel

Light source

1x LED 4,5W 700mA

LED

CRI>90 490 lm 109 2700 K / 3000 K / 3500 K

Driver

Constant Current 700 100~240 V V 50~60 Hz HZ

____ F Dimmable LED

IP20 Bi-volt 50-60Hz

Hanging lamps

Application Packaging

1 Box

0.26 m x 0.26 m x 0.26 m Gross weigth 2.6 Net weigth 2.4 Vol. 0.0175


Lighting effect


Volumetric Diffuser

Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface



Photometric Data





Efficiency Coordinate System **Total Flux** Maximum Value

40.10% CG 490.30 53.76

Other Applications

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty